



BlueSense Transducer

The **BlueSense** transducer facilitates the processing and calculation of measurement values of physical and chemical sensors. In addition, the transducer features a full controller function that can cover all process-oriented tasks.

The BlueSense transducer is compatible with analogue and digital sensors and actuators of all manufacturers.



Application Areas



Drinking Water

- Quality control
- Alarm systems



Wastewater

- Effluent monitoring
- Trend analysis
- Early detection of discharge (fingerprint)



Process Measurement & Control Technology

- Process monitoring in industrial facilities
- Control of process water treatment
- Process optimization



Environmental Monitoring

- River water
- Surface water

Parameters / Sensors

- Blue-green algae
- Chlorine
- Chlorine dioxide
- Chlorophyll a
- Conductivity
- Dissolved organic substances
- Dissolved oxygen
- ISE
- Level
- Oil in water
- Ozone
- pH
- Redox (ORP)
- Salinity
- Temperature
- Turbidity
- Water pressure

Main Functions & Features



Monitoring Function



PID-Controller Function



SD Card Data Logger



2 Sensor Inputs



Intelligent Event Handling



Cloud Data Service



Modular & Expandable



CAN bus, Modbus & Profibus

Technical data

Power supply	12 V DC (9 - 18 V) 24 V DC (18 - 36 V) 230 V AC (90 - 260 V)
Power consumption (typical)	8 W
Dimensions (wxhxd)	23.5 x 18.5 x 11.9 cm
IP protection class	IP 65
Graphic touch display	240 x 128 pixel
Ambient temperature	-10 to +45 °C

Optional interfaces

1x RS-232, RS-485, var. protocols e.g. Modbus
1x CAN bus for connection to ISA, BlueBox, BlueMon & MPS
1x Ethernet [TCP/IP], Modbus [TCP/IP]
Profibus
GPRS / UMTS / LTE modem

Inputs

2x Sensor input for selectable parameters
2x Digital-In (static) potential-free contacts
2x Pulse-In (PNP/NPN selectable)

Outputs

2x Current output 4-20 mA
2x Relay with a switching capacity of 230 V AC/DC; 2 A
2x Relay with a switching capacity of 24 V AC /DC; 0,5 A

Features & functions

PID controller
Signal compensation
Data storage on SD card
Multipoint calibration

Product configuration

The BlueSense transducer can optimally be adapted to the customer specific application through the modular configuration of the sensor inputs.



BlueSense

Art. no. 485 0001